

# CHECK LIST – 2026 - 2027

Nombre del Barco

Número de vela

Teléfono Móvil a bordo

Número de personas a bordo

LUCES DE NAVEGACION FIJAS Y REPUESTO (NO PARA LED)  
Rules 3.27.4 / 3.27.1

EMISORA DE MANO VHF  
Rules 3.29.4

RADIO RECEPTOR PARTES METEO  
Rules 3.29.2

ESPICHES EN CADA PASACASCO  
Rules 4.03

2 EXTINTORES EN DIFERENTES UBICACIONES MÁS MANTA IGNÍFUGA  
Rules 4.05.3

2 BOTES DE HUMO  
Rules 4.23

BOTIQUIN SANITARIO EMERGENCIA Y MANUAL DE PRIMEROS AUXILIOS  
Rules 4.08

SIRENA DE NIEBLA  
Rules 4.09

GPS Y SONDA  
Rules 4.13

REFLECTOR DE RADAR  
Rules 4.10.1

CARTAS NAUTICAS DE LA ZONA DE LA REGATA  
Rules 4.11.2

BOMBA DE ACHIQUE  
Rules 3.23.2

MAYOR CON RIZOS 12,5% O FOQUE TIEMPO DURO  
Rules 4.26.1 /4.27.1

PÚLPITOS Y GUARDAMANCEBOS  
Rules 3.14

1 FONDEO COMPLETO  
Rule 4.06.2

ESQUEMA ELEMENTOS DE SEGURIDAD  
Rules 4.12

COMPAS MAGNETICO FIJO  
Rules 3.24

HERRAMIENTAS, RECAMBIOS Y HERRAMIENTA PARA CORTAR EL APAREJO  
Rules 4.16.1

"HEAVING LINE", O SISGA DE 25 METROS  
Rules 4.22.4

CHALECOS HOMOLOGADOS, SILBATO, NOMBRE  
Rules 5.01

LINTERNA, NAVAJA  
Rules 4.25

2 CUBO CON RABIZA  
Rules 3.23,1

ARO SALVAVIDAS CON LUZ, SILBATO Y ANCLA DE CAPA  
Rules 4.22.3



### MARINE TRANSCIVER OR VHF

OSR reference 3.29.1 / 3.29.8  
Marine radio transceiver with an emergency antenna when the regular antenna depends upon the mast. If VHF min power of 25W, and, if it's installed after 31/12/2015, be DSC capable with an assigned MMSI (unique to the boat) & connected to GPS receiver.



### SOFT TAPERED WOOD PLUGS

OSR reference 4.03  
Soft tapered wood plugs attached or adjacent to every through-hull opening.



### FOGHORN / RIGGING CUTTER / KNIFE STRONG / TOOLS

OSR reference 4.09 / 4.16.1 / 4.16.2 / 4.25  
Foghorn. Rigging cutter. Knife strong, securely restrained, readily accessible from the cockpit.




### HAND-HELD MARINE VHF

OSR reference 3.29.2  
A Hand-held marine VHF transceiver, watertight or with a waterproof cover.



### FIRST AID MANUAL and FIRST AID KIT

OSR reference 4.08  
First aid Kit & Manual (suitable for the conditions and duration of the passage.



### BILGE PUMP

OSR reference 3.23 / 3.23.1 d)  
Bilge pump, manual, permanently installed, operable with all cockpit seats. Removable bilge pumps handle retained by lanyard.



### NAVIGATION LIGHTS

OSR reference 3.27.1 / 2 / 3 / 4  
Navigation lights mounted above sheerline, spare bulbs (not required for LED).



### FIRE EXTINGUISHERS FIRE BLANKET

OSR reference 4.05.1 / 4.05.03  
2 fire extinguishers, ≥ 2kg, dry powder, accessible, different positions.  
Fire blanket near cooking device of open flame.



### BUCKETS

OSR reference 3.23.1 a)  
two strong buckets, each with a lanyard and of at least 9 l (2.4 US Gal) capacity.



### A SECOND RADIO RECEIVER

OSR reference 3.29.4  
A second radio receiver, which maybe the handheld VHF, capable of receiving weather bulletins



### RADAR REFLECTOR

OSR reference 4.10  
Radar reflector: octahedral (with plates circular 12" or rectangular 16") or of min 2m<sup>2</sup> radar cross-section.



### PYROTECHNIC SIGNALS

OSR reference 4.23  
Pyrotechnic signals: 2 orange smoke



**LIFEBUOY**

OSR reference 4.22.3  
Lifebuoy near the helmsman with self-igniting light, yacht's name, retro-reflective material and a drogue.



**HEAVING LINE**

OSR reference 4.22.7  
Heaving line 15-25m long, diameter ≥ 6mm, readily accessible to cockpit.



**LIFE JACKET**

OSR reference 5.01 / 5.01.1 a) i) / 5.01.1 a)  
If manufactured before 2012 shall comply with ISO 12402 - 3 (Level 150) or equivalent, including 396 or UL 1180, if inflatable have a gas inflation system, have crotch/thighstraps (ride up prevention system (RUPS)).  
If manufactured after 2011 shall comply with ISO 12402-3 (Level 150) and be fitted with a whistle, lifting loop, reflective material automatic/manual gas inflation system, crotch/thigh straps (ride up prevention system (RUPS))  
have an emergency position indicating light in accordance with either ISO 12402-8 or SOLAS LSA code 2.2.3, be clearly marked with the boat's or wearer's name  
have a sprayhood in accordance with ISO 12402-8.  
A boat shall carry at least one gas inflatable lifejacket spare cylinder.



**CHARTS G COMPASS**

OSR reference 4.11 / 3.24 a)  
Navigational charts and chart plotting equipment. If electronic-only, an independent alternative shall be on board  
Permanently installed marine magnetic compass.



**HEAVY WEATHER JIB OR REEFABLE MAINSAIL**

OSR reference 4.26.2d)  
Either Heavy Weather Jib or mainsail reefing to reduce the luff by at least 12.5%.

"Por la presente declaro que soy la persona a cargo, que siempre que firme este listado de verificación se ajusta a su Reglamento Especial Offshore asociado (OSR), y que he leído y entiendo las OSR y en particular las reglas 1.02.1 y 1.02.2".

**Nombre de la persona a cargo (OSR 1.02.1)**

**Firma**

**Fecha**

Este documento es un resumen del reglamento OSR de la WORLD SAILING, publicado con la intención de ayudar a los armadores y clubes en la comprobación de los elementos de seguridad. Cualquier duda o detalle de las reglas debe consultarse sobre el documento oficial [www.worldsailing.org](http://www.worldsailing.org)

La aceptación de este documento no reemplaza, sino que complementa lo exigido por capitania marítima o la legislación vigente. La seguridad del barco y su tripulación es responsabilidad de la persona a cargo. El uso de las OSR no garantiza dicha seguridad y únicamente establecen unas mínimas medidas de seguridad por parte de la autoridad organizadora.